

Polyimide Kapton® Tapes

Backing	Adhesive	ESD Property	Peel Strength	Liner Type	Cross Reference	Remark
0.5mil Polyimide	Silicone		21 oz/in			Especially designed for thickness-sensitive applications
1mil Dupont Kapton®	Silicone		25 oz/in		3M 5413 Nitto Permacel P-221AMB	Dupont Kapton® Film
1mil Dupont Kapton®	Silicone	Anti-static	20 oz/in			Dupont Kapton® Film Anti-static
1mil Polyimide	Silicone		25 oz/in		Nitto Permacel P-221 St. Gobain K250 CHR 2345-1	
1mil Polyimide	Silicone	Anti-static	20 oz/in		3M 5419 St. Gobain K290ESD	Anti-static
1mil Polyimide	Acrylic	Anti-static	12.5 oz/in			Anti-static, high temp Acrylic (peak temp 500F)
1mil Dupont Kapton®	Acrylic		25 oz/in		3M 7413 Nitto Permacel P-224AMB	Dupont Kapton® Film
1mil Polyimide	Acrylic		25 oz/in		Nitto Permacel P-224 St. Gobain K103	
1mil Polyimide	Silicone/Silicone		25 oz/in	Clear PET / White PET	Nitto Permacel P-223	Double Coated Polyimide
2mil Polyimide	Silicone		25 oz/in		Nitto Permacel P-222 St. Gobain K350 CHR 2345-2	
2mil Polyimide	Silicone		25 oz/in	2mil PET		Lined version for efficient converting
2mil Polyimide	Acrylic		25 oz/in			2mil Polyimide with Acrylic Adhesive
5mil Polyimide	Silicone		25 oz/in			5mil Polyimide Film Backing

****Above is only a partial list of product SKU's available. Both product modification and new product development available upon request.***